

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	1 / 17

**1. Identification****1.1. Product identifier**

Trade name PERACLEAN® 15

1.2. Recommended use of the chemical and restrictions on use

Relevant applications identified Industrial use

1.3. Details of the supplier of the safety data sheetCompany Hydrus Detergents
2621 7th Avenue South
Estherville, IA. 51334
MFG. Evonik

Telephone 712-765-1060

Telefax 712-765-1062

Email address office@hydrusdetergents.com

1.4. 24 HOUR EMERGENCY TELEPHONE NUMBERS:**CHEMTREC - US & CANADA:** 800-424-9300**CHEMTREC MEXICO:** 01-800-681-9531**CHEMTREC INTERNATIONAL:** +1 703-527-3887 (collect calls accepted)

Product Regulatory Services : 973-929-8060

2. Hazards identification**2.1. Classification of the substance or mixture**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Flammable liquids	Category 4	H227
Acute toxicity (Oral)	Category 4	H302
Acute toxicity (Inhalation)	Category 4	H332
Acute toxicity (Dermal)	Category 4	H312
Skin corrosion	Category 1	H314
Serious eye damage	Category 1	H318
Specific target organ toxicity - single exposure (Respiratory system)	Category 3	H335
Acute aquatic toxicity	Category 1	H400
Chronic aquatic toxicity	Category 1	H410

2.2. Label elements

Statutory basis Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.
Specification
Order Number

161973

Version
Revision date
Print Date
Page

4.1 / US
08/10/2020
06/09/2017
2 / 17

**hazard-defining component(s) (GHS)**

- hydrogen peroxide solution
- Peracetic acid

Symbol(s)



Signal word

Danger

Hazard statement

H227 - Combustible liquid.
H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled.
H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statement:
Prevention

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 - Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 - Wash skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection.

Precautionary statement:
Reaction

P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P363 - Wash contaminated clothing before reuse.
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 - Collect spillage.

Precautionary statement:
Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.

Precautionary statement:
Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other hazards

None known

3. Composition/information on ingredients**• Peracetic acid**

14% - 17%Ø 15%

CAS-No. 79-21-0

Flammable liquids

Organic peroxides

Category 3

Type D

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	3 / 17


HYDRUS
detergents

Acute toxicity (Oral)	Category 3
Acute toxicity (Inhalation)	Category 3
Acute toxicity (Dermal)	Category 4
Skin corrosion	Category 1A
Serious eye damage	Category 1
Specific target organ toxicity - single exposure (Respiratory system)	Category 3
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1
M-factor (aquatic, acute) 1	
M-factor (aquatic, chronic) 10	
• acetic acid...%	24% - 29%
CAS-No. 64-19-7	
• hydrogen peroxide	13% - 15%
CAS-No. 7722-84-1	

Other information

This material is classified as hazardous under OSHA regulations.

4. First aid measures**4.1. Description of first aid measures****General advice**

Pay attention to self-protection.

Remove victims from hazardous area. Immediately remove soiled or soaked clothing and remove it to a safe distance. Keep victim warm, in a stabilized position and covered.

Do not leave victims unattended.

If the casualty is unconscious: Place the victim in the recovery position.

Inhalation

Potential for exposure by inhalation if aerosols or mists are generated.

Move victims into fresh air.

With labored breathing: Provide with oxygen. Consult a doctor.

If the casualty is not breathing: Perform mouth-to-mouth resuscitation, notify emergency physician immediately.

Skin contact

Wash off affected area immediately with plenty of water for at least 15 minutes.

If symptoms persist, consult a physician for treatment.

Eye contact

With eye held open, thoroughly rinse immediately with plenty of water for at least 10 minutes.

Consult an ophthalmologist immediately if the symptoms persist.

When dealing with caustic substances, notify emergency physician immediately (key words: burns in eye).

Ingestion

Rinse mouth.

Immediately give large quantities of water to drink.

Obtain medical attention.

When dealing with caustic substances, notify emergency physician immediately.

4.2. Most important symptoms and effects, both acute and delayed**Symptoms**

Irritation of skin and mucous membranes

Causes burns.

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	4 / 17



daze,
Headache, vertigo, somnolence (sleepiness), nausea.
Health injuries may be delayed.

Hazards

Strongly irritating to corrosive.
Harmful in contact with skin and if swallowed.

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

The initial focus is only on the local action, characterized by quickly progressing deep tissue damage. In the eye, caustic/ irritating and harmful liquids cause, depending on the intensity of exposure, various levels of irritation, destruction, and ablation of the epithelium of the conjunctiva and cornea, corneal clouding, edema and ulcerations.

Danger! Possible loss of eyesight!

Superficial irritations and damage up to ulcerations and scarring develop on the skin.

After accidental absorption in the body, the pathology and clinical findings are dependent on the kinetics of the substance (quantity of absorbed substance, the absorption time, and the effectiveness of early elimination measures (first aid)/ excretion - metabolism).

A specific action of the substance is unknown.

In case of substances with high water solubility, irritations up to formation of necrosis in the upper respiratory tract may result after inhalation of caustic/ irritating aerosols and mists.

The initial focus is on the local action: signs of irritation of the respiratory tract such as coughing, burning behind the sternum, tears, burning in the eyes or nose.

There is a risk of pulmonary edema!

5. Fire-fighting measures**5.1. Extinguishing media**

Suitable extinguishing media: water spray, Foam, dry powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media: organic compounds

5.2. Special hazards arising from the substance or mixture

Contact with the following substances may cause inflammation: flammable substances.

Involved in fire, it may decompose yielding oxygen.

Risk of overpressure and burst due to decomposition in confined spaces and pipes.

Release of oxygen may support combustion. In case of fire, remove the endangered containers and bring to a safe place, if this can be done safely. Keep away from heat.

If necessary:

In the case of fire, cool the containers that are at risk with water or dilute with water (flooding).

5.3. Advice for firefighters

Evacuate personnel to safe areas.

Keep out unprotected persons.

Keep unauthorized persons away.

Water used to extinguish fire should not enter drainage systems, soil or stretches of water.

Ensure there are sufficient retaining facilities for water used to extinguish fire.

Contaminated fire-extinguishing water must be disposed of in accordance with the regulations issued by the appropriate local authorities.

Fire residues should be disposed of in accordance with the regulations.

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. Accidental release measures

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	5 / 17

**6.1. Personal precautions, protective equipment and emergency procedures**

Product causes chemical burns. Wear personal protective equipment; see section 8. Evacuate personnel to safe areas. Keep out unprotected persons. Keep unauthorized persons away. Remove all sources of ignition. Ventilate the area.

6.2. Environmental precautions

Observe regulations on prevention of water pollution (collect, dam up, cover up). Do not allow to run into water channels, surface water, or into the ground. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, rivers, groundwater or soil.

6.3. Methods and material for containment and cleaning up

Keep away from incompatible substances. Keep away from flammable substances. see section 10. Clean contaminated surface thoroughly. Recommended cleaning agent: water. Dispose of absorbed material in accordance with the regulations. see section 13. With small amounts: Dilute product with lots of water and rinse away. see section 12. or Absorb with liquid-binding material, e. g.: chemisorption, diatomaceous earth, universal binder Do not use: textiles, saw dust, combustible substances. Pick up mechanically. Collect in suitable containers.

Additional advice

Make safe or remove all sources of ignition.

Isolate defective containers immediately, if possible and safe to do.

Shut off leak, if possible and safe to do.

Place defective containers in waste receptacle (waste packaging receptacle) made of plastic (not metal).

Do not seal defective containers or waste receptacles airtight (danger of bursting due to product decomposition).

Product taken out should not be returned into container.

Never return spilled product into its original container for re-use. (Risk of decomposition.).

7. Handling and storage**7.1. Precautions for safe handling**

Avoid contact with skin, eyes and clothing. Do not breathe in vapours, aerosols, sprays. For personal protection see section 8. Handle in accordance with good industrial hygiene and safety practice. Avoid impurities and heat effect. Ensure there is good room ventilation. Immediately change moistened and saturated work clothes. Immediately rinse contaminated or saturated clothing with water. Never return spilled product into its original container for re-use. (Risk of decomposition.). Provide for installation of emergency shower and eye bath. Set up safety and operation procedures.

7.2. Conditions for safe storage, including any incompatibilities**Advice on protection against fire and explosion**

Avoid sun rays, heat, heat effect.

Keep away from sources of ignition - No smoking.

Keep away from flammable substances.

Keep away from incompatible substances.

see section 10.

To cool, spray closed containers with water spray jet. In case of fire, remove the endangered containers and bring to a safe place, if this can be done safely.

see section 5.

Storage

cool, well ventilated, clean, lockable.

Recommendation: Acid-proof floor.

Only use containers which are specially permitted for: Peracetic acid.

and/or

For transport, storage and tank installations only use suitable materials.

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	6 / 17



Use adequate venting devices on all packages, containers and tanks and check correct operation periodically.

Do not confine product in unvented vessels or between closed valves.

Risk of overpressure and burst due to decomposition in confined spaces and pipes.

Packages, containers and tanks should regularly be checked by visual observation for any sign of abnormality, e.g. corrosion, exert pressure (bulging), temperature increase etc.

Transport and store container in upright position only.

Do not empty container by means of pressure.

Always close container tightly after removal of product.

Do not keep the container sealed.

Ensure tightness at all times. Avoid leakage.

Avoid residues of the product on the containers.

Suitable materials stainless steel (1.4571)

Suitable materials polyethylene, polypropylene, polyvinyl chloride (PVC),

Suitable materials polytetrafluoroethylene, glass, ceramics.

Unsuitable materials Iron, Copper, brass, Bronze, Aluminium, tin, zinc.

Further information

Avoid sun rays, heat, heat effect.

Avoid impurities.

see also section 15.

Regularly verify the availability of water to deal with emergencies (for cooling, tank flooding, fire fighting) and check correct operation periodically.

For detailed information on design specifications for the construction of tank- and dosing installations ask the producer for advice.

Advice on common storage

Do not store together with: alkalis, reductants, metallic salts (risk of decomposition).

Do not store together with: inflammable substances (risk of fire).

8. Exposure controls/personal protection**8.1. Control parameters**

• acetic acid...%		
CAS-No.	64-19-7	
Control parameters	15 ppm	Short Term Exposure Limit (STEL):(ACGIH)
Control parameters	10 ppm	Time Weighted Average (TWA):(ACGIH)
Control parameters	10 ppm 25 mg/m3	Permissible exposure limit:(OSHA Z1)
Control parameters	15 ppm 37 mg/m3	Short Term Exposure Limit (STEL):(US CA OEL)
Control parameters	40 ppm	Ceiling Limit Value:(US CA OEL)
Control parameters	10 ppm 25 mg/m3	Time Weighted Average (TWA) Permissible Exposure Limit (PEL)(US CA OEL)
• hydrogen peroxide		
CAS-No.	7722-84-1	
Control parameters	1 ppm	Time Weighted Average (TWA):(ACGIH)
Control parameters	1 ppm 1.4 mg/m3	Permissible exposure limit:(OSHA Z1)
Control parameters	1 ppm 1.4 mg/m3	Time Weighted Average (TWA) Permissible Exposure Limit (PEL)(US CA OEL)

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	7 / 17

**8.2. Exposure controls****Engineering measures**

Ensure suitable suction/aeration at the work place and with operational machinery.
Provide for installation of emergency shower and eye bath.
see also section 7.

Personal protective equipment**Respiratory protection**

Do not inhale vapour, aerosols, mist.
If workplace exposure limit is exceeded apply Respiratory protective equipment.
wear a self contained respiratory apparatus
If necessary: Local ventilation.
A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.
Note time limit for wearing respiratory protective equipment.

Hand protection

Applies to handling for brief periods or of small amounts
Glove material Nitrile, for example: Dermatril 740, Kächele-Cama Latex GmbH (KCL), Germany
Material thickness 0.11 mm
Break through time 10 min
Method DIN EN 374
Applies to handling for longer periods or of large amounts
Glove material Polychloroprene (PCP), for example: Camapren 720, Kächele-Cama Latex GmbH (KCL), Germany
Material thickness 0.65 mm
Break through time > 480 min
Method DIN EN 374

The above mentioned hand protection is based on knowledge of the chemistry and anticipated uses of this product but it may not be appropriate for all workplaces. A hazard assessment should be conducted prior to use to ensure suitability of gloves for specific work environments and processes prior to use.
Use impermeable gloves.

Personal protective equipment that provides a barrier to prevent dermal exposure to this substance is required.

Eye protection

Use chemical splash goggles or face shield.
When handling larger quantities: protective screen

Skin and body protection

Wear protective clothing, acid-proof.
Suitable materials are:
PVC, neoprene, nitrile rubber (NBR), rubber.
Rubber or plastic boots

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

Hygiene measures

Avoid contact with skin, eyes and clothing.
Do not inhale vapour, aerosols, mist.
Ensure there is good room ventilation.

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	8 / 17



Avoid contaminating clothes with product.
Immediately change moistened and saturated work clothes.
Immediately rinse contaminated or saturated clothing with water.
Any contaminated protective equipment is to be cleaned after use.
No eating, drinking, smoking, or snuffing tobacco at work.
Wash face and/or hands before break and end of work.
Use barrier cream regularly.

Protective measures

Handle in accordance with good industrial hygiene and safety practice.
Wear suitable protective clothing, gloves and eye/face protection.
The work-place related airborne concentrations have to be kept below of the indicated exposure limits.
If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

physical state	liquid
Colour	colourless, clear
Form	liquid
Odour	stinging
Odour Threshold	no data available
pH	ca. -0.6 (20 °C) Medium: Product
Melting point/range	ca. -50 °C
Boiling point/range	not applicable > 60 °C Decomposition
Flash point	79 °C (closed cup) Method: ISO 2719
Evaporation rate	no data available
Flammability (solid, gas)	no data available
Lower explosion limit	no data available
Upper explosion limit	no data available
Vapour pressure	ca. 25 hPa (20 °C)
Relative vapour density	no data available
Density	ca. 1.15 g/cm ³ (20 °C)
Water solubility	no data available
Partition coefficient: n-	log Pow: -0.52

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	9 / 17



octanol/water Measured as peracetic acid

Autoignition temperature 260 °C
Method: DIN 51 794

Thermal decomposition No data available

Viscosity, dynamic no data available

9.2. Other information

Explosiveness No data available

Metal corrosion No data available

Other information strong oxidizing agent
oxidizing
(according to EC Directive 67/548/EEC)

10. Stability and reactivity**10.1. Reactivity**

Risk of self-accelerating, exothermic decomposition with the development of oxygen, at, Effect of thermal energy / heat.

Product is a(n) oxidizing agent and reactive.

10.2. Chemical stability

Stable under recommended storage conditions.

Product is supplied in stabilised form.

10.3. Possibility of hazardous reactions

Stability Stable under recommended storage conditions.

Possibility of hazardous reactions Product is a(n) oxidizing agent and reactive.

Product is supplied in stabilised form.

Danger of decomposition if exposed to heat

When coming in contact with the product, impurities, decomposition catalysts, metallic salts, alkalis, reducing agents may lead to self-accelerated, exothermic decomposition and the formation of oxygen.

Risk of overpressure and burst due to decomposition in confined spaces and pipes.

Release of oxygen may support combustion.

10.4. Conditions to avoid

sun rays, heat, heat effect

10.5. Incompatible materials

Impurities, decomposition catalysts, metal salts, alkalis, reducing substances., metals, nonferrous heavy metal, aluminium, zinc., Possible hazardous reaction: decomposition.

Flammable materials, Possible hazardous reaction: Spontaneous ignition.

organic solvents, Possible hazardous reaction: Danger of explosion.

10.6. Hazardous decomposition products

decomposition products Under conditions of thermal decomposition:

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	10 / 17



Steam, Oxygen

11. Toxicological information**11.1. Information on toxicological effects**

Acute oral toxicity	LD50 Rat: 1015 mg/kg Method: OECD Test Guideline 401 Test substance: Peracetic acid 15 %
Acute inhalation toxicity	Approximate lethal concentration Rat: 0.49 mg/l Vapour as peracetic acid Acute toxicity estimate : 20 mg/l / 4 h / vapour Method: Calculation method
Acute dermal toxicity	LD50 Rabbit (female): 1912 mg/kg Method: literature Test substance: peracetic acid 10 %
Skin irritation	Rabbit strongly corrosive Method: literature Test substance: peracetic acid 10 %
Eye irritation	Rabbit Corrosive Method: literature Test substance: peracetic acid 5 %
Sensitization	Buehler Test Guinea pig: negative Method: literature Test substance: peracetic acid 5 %
Repeated dose toxicity	Oral Rat Testing period: 90 d target organ/effect: Local irritant effect Method: OECD TG 408 Test substance: peracetic acid 5 %
Gentoxicity in vitro	Ames test predominantly negative Metabolic activation: with or without (literature value) Unscheduled DNA synthesis -test (UDS) negative Metabolic activation: without (literature value) chromosomal aberration V 79 cells negative Metabolic activation: with or without Method: OECD TG 473

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	11 / 17



	HGPRT-Test V 79 cells negative Metabolic activation: with or without Method: OECD TG 476
Gentoxicity in vivo	Micronucleus test Mouse Oral negative Method: literature
	Unscheduled DNA synthesis -test (UDS) Rat Oral negative Method: literature
Teratogenicity	Rat NOAEL (No Observed Adverse Effect Level) teratogenesis: 30.4 mg/kg NOAEL maternal (No Observed Adverse Effect Level): 12.5 mg/kg Method: OECD TG 414 Low body weight Disturbed ossification No indication of development toxicity in maternally non-toxic doses.
Human experience	Caustic / irritant effect on skin, eyes and mucous membranes (respiratory tract) Also in dilute solutions Onset of effects within seconds or minutes depending on the concentration.

12. Ecological information**12.1. Toxicity**

Toxicity to fish	LC50 Pleuronectes platessa: 11 mg/l / 96 h Method: literature Related to substance: As peracetic acid
	LC50 Oncorhynchus mykiss: 1 - 2 mg/l / 96 h Method: literature Related to substance: As peracetic acid
	NOEC Daphnia magna: 1 mg/l / 48 h Test substance: PAA solution (ca. 15% PAA, ca. 15% H2O2, ca. 25% HOAc) Method: OECD TG 202
	EC50 Daphnia magna: 3.3 mg/l / 48 h Test substance: PAA solution (ca. 15% PAA, ca. 15% H2O2, ca. 25% HOAc) Method: OECD TG 202
Toxicity in aquatic	EC50 Daphnia magna: 0.5 - 1.1 mg/l / 48 h

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	12 / 17



invertebrates	Method: OECD TG 202 (literature value) Related to substance: As peracetic acid
Toxicity to algae	IC 50 selenastrum capricornutum: ca. 0.18 mg/l / 120 h Method: US-EPA-method chronic (literature value) Related to substance: As peracetic acid
Toxicity to bacteria	EC50 Activated sludge: 5.1 mg/l / 3 h Method: OECD TG 209 Related to substance: As peracetic acid
chronic toxicity in fish	NOEC Danio rerio: 0.015 mg/l / 33 d Test substance: As peracetic acid Method: OECD TG 210
chronic toxicity in daphnia	NOEC Daphnia magna: 0.05 mg/l / 21 d Method: OECD 211 As peracetic acid
Toxicity in organisms which live in the soil	LC50 Eisenia foetida: > 1000 mg/kg / 14 d Method: OECD 207 Related to substance: Peracetic acid 15 % EC50 C-Transformation : > 933.6 mg/kg / 28 d Method: OECD TG 217 Related to substance: peracetic acid EC50 N-Transformation : > 933.6 mg/kg / 28 d Method: OECD TG 216 Related to substance: peracetic acid
Toxicity in terrestrial plants	NOEC : 180 mg/kg Test period: 14 d Method: OECD 208

12.2. Persistence and degradability

Biodegradability	Exposure time: 28 d Result: Readily biodegradable Method: OECD TG 301 E At non-bacteriotoxic concentrations inoculum: seawater Exposure time: 28 d Result: 95 % completely biodegradable Method: OECD 306
Physico-chemical removability	Hydrolyzes after 7 days by approx. 50 %. pH 4 Hydrolyzes after 1 day to approx. 50 %. pH 7 and pH 9

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	13 / 17



AOX The product does not contain any organically bonded halogen.

Further Information Under ambient conditions quick hydrolysis, Reduction or decomposition occurs.
The following substances are formed: oxygen, water, acetic acid.
Acetic acid is easily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation low
log Pow: see chapter 9

12.4. Mobility in soil**12.5. Other adverse effects**

Further Information Does not contain any heavy metals and compounds from EC directive 76/464
e.g. arsenic-, lead
cadmium
Mercury
organic halogen compounds
organic compounds

Ecotoxicology Assessment**· Peracetic acid**

Acute aquatic toxicity Very toxic to aquatic life.
Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

13. Disposal considerations**13.1. Waste treatment methods****Product**

Waste must be disposed of in accordance with local, state, provincial and federal laws and regulations. Empty containers must be handled with care due to product residue.

Uncleaned packaging

Rinse empty containers before disposal; recommended cleaning agent: water.
Offer rinsed packaging material to local recycling facilities. Dispose of containers that have not been emptied completely and/or cleaned like of substance.

14. Transport information**D.O.T. Road/Rail**

14.1. UN number: UN 3109
14.2. UN proper shipping name: Organic peroxide type F, liquid (Peroxyacetic acid, type F stabilized - 14 - 17%, contains acetic acid)
14.3. Transport hazard class(es): 5.2 (8)

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	14 / 17



- 14.4. Packing group: II
14.5. Environmental hazards (Marine pollutant): --
14.6. Special precautions for user: Yes
Keep separate from alkalis, powdered metals and flammable substances.

Air transport ICAO-TI/IATA-DGR

- 14.1. UN number: UN 3109
14.2. UN proper shipping name: Organic peroxide type F, liquid(contains PEROXYACETIC ACID, TYPE F, stabilized)
14.3. Transport hazard class(es): 5.2 (8)
14.4. Packing group: --
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
IATA-C: ERG-Code 5L
Must be protected from direct sunlight and stored away from all sources of heat in a well-ventilated area.
IATA-P: ERG-Code 5L
Must be protected from direct sunlight and stored away from all sources of heat in a well-ventilated area.
Keep separate from alkalis, powdered metals and flammable substances.

Sea transport IMDG-Code/GGVSee (Germany)

- 14.1. UN number: UN 3109
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID(contains PEROXYACETIC ACID, TYPE F, stabilized)
14.3. Transport hazard class(es): 5.2 (8)
14.4. Packing group: --
14.5. Environmental hazards (Marine pollutant): --
14.6. Special precautions for user: Yes
EmS: F-J,S-R
"Separated from" acids and alkalis.
Protected from sources of heat.
Keep separate from alkalis, powdered metals and flammable substances.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: for transport approval see regulatory information

15. Regulatory information**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- None listed

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	15 / 17

**CERCLA Reportable Quantities**

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- acetic acid...%
CAS-No. 64-19-7
Reportable Quantity 31250 lbs

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Fire Hazard

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- Peracetic acid
CAS-No. 79-21-0

Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

State Regulations**California Proposition 65**

A warning under the California Drinking Water Act is required only if listed below:

- None listed

International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

Europe (EINECS/ELINCS)	listed/registered
Switzerland	listed/registered
USA (TSCA)	listed/registered

An employer using HMIS/NFPA labeling must through training ensure that its employees are fully aware of the hazards of the chemicals used.

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	08/10/2020
Order Number		Print Date	06/09/2017
		Page	16 / 17

**HMIS Ratings**

Health :	3
Flammability :	2
Physical Hazard :	1

NFPA Ratings

Health :	3
Flammability :	2
Reactivity :	1

16. Other information**Further information**

Further information Data for the production of the safety data sheet from the studies available and from the literature.
Further information about the characteristics of the product can be found in the product code of practice or in the Product-Brochure .

Revision date 08/10/2020

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Legend

ACC	American Chemistry Council
ACGIH	American Conference of Governmental Industrial Hygienists
ACS	Advisory Committee on Sustainability
ADI	Acceptable Daily Intake
ASTM	American Society for Testing and Materials
ATP	Adaptation to Technical Progress
BCF	Bioconcentration factor
BOD	Biochemical oxygen demand
c.c.	closed cup
CAO	Cargo Aircraft Only
Carc	Carcinogen
CAS	Chemical Abstract Services
CDN	Canada
CEPA	Canadian Environmental Protection Act
CERCLA	Comprehensive Environmental Response – Compensation and Liability Act
CFR	Code of Federal Regulations
CMR	carcinogenic-mutagenic-toxic for reproduction
COD	Chemical oxygen demand
DIN	German Institute for Standardization
DMEL	Derived minimum effect level

SAFETY DATA SHEET**PERACLEAN® 15**

Material no.		Version	4.1 / US
Specification	161973	Revision date	01/06/2017
Order Number		Print Date	06/09/2017
		Page	17 / 17



DNEL	Derived no effect level
DOT	Department of Transportation
EC50	half maximal effective concentration
EPA	Environmental Protection Agency
ErC50	Reduction of Growth Rate
ERG	Emergency Response Guide Book
FDA	Food and Drug Administration
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
GLP	Good Laboratory Practice
GMO	Genetic Modified Organism
HCS	Hazard Communication Standard
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
ICAO-TI	International Civil Aviation Organization- Technical Instructions
ICCA	International Council of Chemical Association
ID	Identification number
IMDG	International Maritime Dangerous Goods
IUPAC	International Union of Pure and Applied Chemistry
ISO	International Organization For Standardization
LC50	50 % Lethal Concentration
LD50	50 % Lethal Dose
L(EC50)	LC50 or EC50
LOAEL	Low est observed adverse effect level
LOEL	Low est observed effect level
MARPOL	International Convention for the Prevention of Pollution from Ships
NFPA	National Fire Protection Association
NOAEL	No observed adverse effect level
NOEC	no observed effect concentration
NOEL	no observed effect level
o. c.	open cup
OECD	Organisation for Economic Cooperation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration
PBT	Persistent, bioaccumulative, toxic
PEC	Predicted effect concentration
PNEC	Predicted no effect concentration
RQ	Reportable Quantity
SDS	Safety Data Sheet
STOT	Specific Target Organ Toxicity
UN	United Nations
vPvB	very persistent, very bioaccumulative
voc	volatile organic compounds
WHMIS	Workplace Hazardous Materials Information System
WHO	World Health Organization